

PRODUCT SPECIFICATIONS

	Roll S	lize	
THICKNESS: 14MIL +/- 5%		MIL +/- 5%	
WIDTH	ΓH: 66" + ½" – 0"		,
LENGTH: 1		1 YARDS	
NET WEIGHT: 150		LBS.* +/- 3%	· · · · · · · · · · · · · · · · · · ·
YARD YIE	LD: .67	.673	
	Material 1	Description	
FINISH: DOUBL		JBLE POLISHED	
HAND: SOF		T - 2S	
COLOR: AZTEC RED,		EC RED, YELLO	W,
BLUE, DARK GREEN SHADE 8, CHARCOAL			
Special Features			
WELD SCREEN TINTED			
CALIFORNIA FIRE MARSHAL FIRE RATING			
UV STABILIZED			
-0° F COLD CRACK			
LIGHTLY DUSTED			
Physical Properties			
Tensile Strength	MD	2700	ASTM-D-882
(PSI)	CD	2550	AS 1 WI-D-882
Elongation	MD	240	ASTM-D-882
(%)	CD	260	
Tear Strength	MD	330	ASTM-D-1004
(Lbs./in)	CD	330	
Heat Shrinkage	MD	- 5	ASTM-D-1004
(%)	CD	+2	
Shipped in a box, r	olled in craft paper	on 3" I.D. Cores	

^{*} Shipping weight: Add 12 lbs to net weight

Note: The information contained herein is believed to be reliable but no representations, guaranties or warranties of any kind are made to its accuracy or suitability for particular applications.